



Jacks

360° Rotational Toe Jacks

- Equal capacity on head and toe
- Can be used in any position
- Lifting by means of an integral hand pump
- Pressure control valve for a longer service life of the jack
- Low claw height
- Large base plate for a high level of stability

Product Code	Model	Capacity (t)	Lift (mm)	Minimum Claw Height (mm)	Minimum Head Height (mm)	Effort Required at Full Load (daN)	Weight (kg)
H310311005	MH 50	5	205	25	368	38	25.0
H310310010	MH 100	10	230	30	420	40	35.0
H310311025	MH 250	25	215	58	505	40	109.0



Multi-Purpose Superjacks

- Lightweight construction
- Stroke limiting device

Product Code	Model	Capacity (t)	Closed Height (mm)	Stroke (mm)	Base Length (mm)	Base Width (mm)	Weight (kg)
H310321003	JAS103	10	131	75	162	75	4.3
H310321005	JAS105	10	181	125	162	75	5.7



Compact Jacks

- Spring assisted return piston
- Sealed hydraulic system

Product Code	Model	Capacity (t)	Closed Height (mm)	Stroke (mm)	Piston Dia. (mm)	Max Handle Height (mm)	Length (mm)	Width (mm)	Weight (kg)
H310361035	JCS10	10	76	35	38	266	240	70	4.5
H310362041	JCS20	20	102	41	51	281	257	102	5.5
H310363045	JCS30	30	112	45	60	285	281	125	8.0



Hollow Piston Jacks

- Operates in any position
- Ideal for pulling applications

Product Code	Model	Capacity (t)	Closed Height (mm)	Stroke (mm)	Piston Dia (mm)	Max Handle Height (mm)	Centre Hole (mm)	Length (mm)	Width (mm)	Weight (kg)
H310371341	JCH13	13	95	41	51	281	25	257	102	5.5
H310372145	JCH21	21	114	45	60	285	35	281	125	8.0