



Lever Hoists

SS11 Subsea Lever Hoist

- Range from 0.8t to 20t
- Patented Quad Cam Pawl System
- Double switch brake mechanism
- One piece construction pinion gear
- Marine specific friction discs
- Fully corrosion protected body and components
- Adaptable to use both inverted and horizontally
- Brake chamber protection from outside contamination

Product Code	Model	Capacity (t)	Effort (kg)	Dimensions (mm)							Load Chain		Std HOL (m)	Weight at Std HOL (kg)	Weight for Extra Metre HOL (kg)
				A	B	C	D	E	F1	F2	Diameter (mm)	No. of Falls			
H060160815	SS-0080	0.8	23	128	243	295	158	99	28	45	6.3	1	3	9.1	0.9
H060161515	SS-0150	1.5	26	154	370	320	172	104	34	51	7.1	1	3	12.6	1.1
H060163015	SS-0300	3.0	38	182	370	400	195	108	36	56	10.0	1	3	22.0	2.2
H060166015	SS-0600	6.0	40	242	370	570	195	108	49	70	10.0	2	3	34.5	4.3
H060170015	SS-1000	10.0	47	379	370	630	195	108	54	87	10.0	3	3	55.0	6.5
H060175015	SS-1500	15.0	44	566	370	840	195	108	59	81	10.0	5	3	128.0	10.9
H060180015	SS-2000	20.0	49	470	370	1050	250	160	81	110	10.0	6	3	174.0	13.0

