



Manhole Lifting Equipment

SRG Manhole Clamps

- For lifting manhole rings and cones
- Easy slinging and releasing through permanent opener
- No adjustment of clamping range necessary
- Will lift 800mm to 2000mm diameter units

Product Code	Model	Nominal Value ID of Cones and Manholes (mm)	Number of Claws	Gripping Range of Claws (mm)	Working Load Limit WLL (kg)	Weight (kg)
H551210015	SRG-UNI-1.5	800 - 2000	3	40 - 120	1500	28.0
H551210030	SRG-UNI-3	800 - 2000	3	60 - 180	3000	40.0



SVZ-UNI-UK

- Manhole and cone installation clamp
- Ultimate in safety in gripping by means of self-tensioning steel claws, which grip inside the manhole ring
- An additional operator is not necessary, as the driver of the lifting machine "switches" the grab from gripping to releasing
- Will lift inside diameter 900mm to 1500mm
- Extension arms can be fitted to increase to 1800mm inside diameter
- Capacity is 2500kg

Product Code	Model	Nominal Width (mm)	Working Load Limit WLL (kg)	Weight (kg)
H551300025	SVZ-UNI-UK	900 - 1500	2500	96.0



Manhole Pipe Lifting Pins

- Manhole pipe lifting pins have been designed and made specifically to lift and position safely concrete manhole chambers
- The unique quick release feature enables the ground workers to complete the installation without additional tools
- Speeds lifting operations
- No threads to protect or nuts to safeguard
- Four standard sizes to suit most manhole pins

Product Code	Model	Dia. (mm)	Capacity each (kg)	Capacity Set of 3 (kg)	Weight (kg)
H551000030	HLP32	32	1000	3000	2.4
H551000045	HLP35	35	1500	4500	3.2
H551000060	HLP38	38	2000	6000	3.9