

# Modulift Spreader Beams

## MOD 24 Spreader Beams

- Rated at 24t SWL at 5m span (30° STV)
- 'Sling to Vertical' angle, 45° or less
- End Units and Drop Links are rated at 12t WLL each

Please refer to the table below for load ratings at alternative sling to vertical (STV) angles and beam lengths.

Span (m)	MOD 24					
	Sling to Vertical Angle (STV)					
	45°		30°		20°	
	SWL (t)	Min. Top Sling Length (m)	SWL (t)	Min. Top Sling Length (m)	SWL (t)	Min. Top Sling Length (m)
1.0	24	0.6	24	0.9	24	1.3
1.5	24	0.9	24	1.4	24	2.1
2.0	24	1.3	24	1.9	24	2.8
2.5	24	1.7	24	2.4	24	3.5
3.0	24	2.0	24	2.9	24	4.3
3.5	24	2.4	24	3.4	24	5.0
4.0	23	2.7	24	3.9	24	5.7
4.5	19	3.1	24	4.4	24	6.5
5.0	16	3.4	24	4.9	24	7.2
5.5	13	3.8	23	5.4	24	7.9
6.0	11	4.1	19	5.9	24	8.7
6.5	9	4.5	16	6.4	24	9.4
7.0	8	4.8	14	6.9	22	10.1
7.5	6	5.2	12	7.4	19	10.8
8.0	6	5.5	11	7.9	16	11.6

MOD 24			
Product Code	Model	Description	Weight Item (kg)
H050220240	P1	End Unit	17
H050230240	P2	Drop Link	5
H050250248	P3	2.0m Strut	41
H050250246	P4	1.0m Strut	24
H050250243	P5	0.5m Strut	16
H550210170	P6	17t Safety Shackle	8
H550210120	P7	12t Safety Shackle	5
	P8	M20 x 50, Grade 8.8 HT Bolts, Nuts & Washers	

