



# Skoots & Stairclimbers

## Skoots Moving System

- Economic, simple, manoeuvrable and safe, Skoots are simple to operate and requires minimal training
- Secure the load to the eyebolts fitted to the Skoots frame using both straps supplied
- Pump the handle on the hydraulic jack to raise the load
- Move the load into position, using the directional locks on the castor if required
- Lower the load with accuracy using the valve wheel on the jacks

Product Code	Model	Lifting Height (mm)	Castors Single Solid Nylon Wheels (mm)	Castors Twin Solid Nylon Wheels (mm)	Strap Length (m)	Hydraulic Jack Max Lift (mm)	Toe Plate Size (mm)	Load Capacity (kg)	Height (mm)	Width (mm)	Weight Pair (kg)
H250300002	SK2000	400	125	-	3.8	400	380 x 120	2000	1160	510	102.0
H250300005	SK5000	200	-	150	4.5	200	600 x 150	5000	1170	790	232.0



## L1 & M1 Stairclimbers

- Speeds loading and delivery
- Operates on tight landings
- Eliminates product and premises damage
- Minimises physical effort and strain
- One-man operation reduces manpower
- In-transit charging kit

Product Code	Model	Maximum Capacity (kg)	Maximum Height Deck / Dock (mm)	Toe Plate (mm)	Overall Width (WxDxH) (mm)	Electronic Charger (V/amp)	Truck Construction	Wheels Dia. (mm)	Gel Filled Leak Proof Battery (V/amp)	Weight (kg)
H410920295	L1	295	840	600x100	610x420x1520	220/240 – 4amp	Aluminium	200	12/20	45.0
H410930680	M1	680	840	610x150	685x430x1520	220/240 – 4amp	Steel	200	12/30	75.0



## MTK Series Stairclimbers

- Highly portable
- Push button control
- Quick connect safety straps
- Removable battery for easy changing
- Adjustable handle for varying load heights
- One man operation reduces manpower

Product Code	Model	Maximum Capacity (kg)	Overall Height (mm)	Overall Height (folded) (mm)	Overall Width (mm)	Pneumatic Tyres (mm)	Battery	Weight Excluding Battery (kg)
H410910190	MTK190	190	1520	1100	510	260 x 85	24V 6.5AH	32.0
H410910310	MTK310	310	1620	1100	580	260 x 85	24V 6.5AH	35.0

