



Alloy Bow Shackles

Standard Green Pin Alloy Shackles

- Body and pin high tensile steel, Grade 6, quenched and tempered
- Screw pin and Safety pin options
- Safety Factor: MBL equals 6 x WLL
- Hot dipped galvanised
- Temp -20°C to 200°C
- EC declaration of conformity. (Upon request basic raw material cert, manufacturer test cert, inspection cert & DNV cert.)

Product Code	Model	Working Load Limit (t)	Body dia (mm)	Pin Dia. (mm)	Eye Dia. (mm)	Inside Width (mm)	Inside Length (mm)	Bow Width (mm)	Weight Each (kg)
H550200005	Screw	0.5	7	8	16.5	12	29	20	0.06
H550210005	Safety								
H550200007	Screw	0.75	9	10	20	13.5	32	22	0.11
H550210007	Safety								
H550200010	Screw	1	10	11	22.5	17	36.5	26	0.16
H550210010	Safety								
H550200015	Screw	1.5	11	13	26.5	19	43	29	0.22
H550210015	Safety								
H550200020	Screw	2	13.5	16	34	22	51	32	0.42
H550210020	Safety								
H550200032	Screw	3.25	16	19	40	27	64	43	0.74
H550210032	Safety								
H550200047	Screw	4.75	19	22	46	31	76	51	1.2
H550210047	Safety								
H550200065	Screw	6.5	22	25	52	36	83	58	1.8
H550210065	Safety								
H550200085	Screw	8.5	25	28	59	43	95	68	2.6
H550210085	Safety								
H550200095	Screw	9.5	28	32	66	47	108	75	3.7
H550210095	Safety								
H550200120	Screw	12	32	35	72	51	115	83	4.9
H550210120	Safety								
H550200135	Screw	13.5	35	38	80	57	133	92	6.5
H550210135	Safety								
H550200170	Screw	17	38	42	88	60	146	99	8.2
H550210170	Safety								
H550200250	Screw	25	45	50	103	74	178	126	14.2
H550210250	Safety								
H550200350	Screw	35	50	57	111	83	197	138	19.9
H550210350	Safety								
H550200425	Screw	42.5	57	65	130	95	222	160	28.3
H550210425	Safety								
H550200550	Screw	55	65	70	145	105	260	180	39.6
H550210550	Safety								
H550200850	Screw	85	75	83	162	127	329	190	62.0
H550210850	Safety								

