



Super Alloy Shackles

Polar/Super Green Pin Alloy Shackle

- Body and pin high tensile steel, Grade 8, quenched and tempered
- Safety Factor: MBL equals 5 x WLL
- EN 13889 & meets performance requirements of US Fed Spec RR-C-271, Type IVA Class 3, Grade B
- Hot dipped galvanised
- Temp -40°C to 200°C
- EC declaration of conformity. (Upon request basic raw material cert, manufacturer test cert & works cert.)

Product Code	Working Load Limit (t)	Body Dia. (mm)	Pin Dia. (mm)	Eye Dia. (mm)	Inside Width (mm)	Inside Length (mm)	Bow Width (mm)	Overall Length (mm)	Bolt Length (mm)	Overall Width (mm)	Weight Each (kg)
H550230033	3.3	13.5	16	34	22	51	32	89	82	58	0.5
H550230050	5	16	19	40	27	64	43	110	98	75	0.8
H550230070	7	19	22	46	31	76	51	129	114	89	1.3
H550230095	9.5	22	25	52	36	83	58	144	130	102	1.9
H550230125	12.5	25	28	59	43	95	68	164	150	118	2.8
H550230150	15	28	32	66	47	108	75	185	166	131	3.9
H550230180	18	32	35	72	51	115	83	201	178	147	5.2
H550230210	21	35	38	80	57	133	92	227	197	162	6.9
H550230300	30	38	42	88	60	146	99	249	202	175	8.8
H550230400	40	45	50	103	74	178	126	300	249	216	15.0
H550230550	55*	57	57	117	83	197	138	341	286	252	22.7
H550230850	85*	70	70	143	105	260	180	437	344	320	43.2
H550231200	120*	83	83	162	127	329	190	535	403	356	70.5
H550231500	150*	95	95	208	147	400	238	647	511	428	110.0
H550231750	175	105	108	238	169	410	275	688	561	485	160.0

