

Synthetic Slings

Duplex & Quadplex Webslings

Webslings available up to 48t capacity



Sling Type / Colour Code				Basket Hitch			
Roundsling (RS) Duplex (DX), Quadplex (QP) Quadplex Side by Side (QPS)	Webbing Width (mm)			Parallel M' = 2	90° M' = 1.4		
RS/DX	30	1.0	0.8	2.0	1.4	1.4	2.0
RS/DX	60	2.0	1.6	4.0	2.8	2.8	4.0
RS/DX	90	3.0	2.4	6.0	4.2	4.2	6.0
RS/DX	120	4.0	3.2	8.0	5.6	5.6	8.0
RS/DX	150	5.0	4.0	10.0	7.0	7.0	10.0
RS/DX	180	6.0	4.8	12.0	8.4	8.4	12.0
RS/DX	240	8.0	6.4	16.0	11.2	11.2	16.0
RS/DX	299	10.0	8.0	20.0	14.0	14.0	20.0
RS/DX	300	12.0	9.6	24.0	16.8	16.8	24.0
RS	-	15.0	12.0	30.0	21.0	21.0	30.0
QP	240	16.0	12.8	32.0	22.4	22.4	32.0
RS/QP	299	20.0	16.0	40.0	28.0	28.0	40.0
QP	300	24.0	19.2	48.0	33.6	33.6	48.0
RS	-	25.0	20.0	50.0	35.0	35.0	50.0
RS	-	30.0	24.0	60.0	42.0	42.0	60.0
QPS	480	32.0	25.6	64.0	44.8	44.8	64.0
RS/QPS	598	40.0	32.0	80.0	56.0	56.0	80.0
QPS	600	48.0	38.4	96.0	67.2	67.2	96.0
RS	-	50.0	40.0	100.0	70.0	70.0	100.0
RS	-	60.0	48.0	120.0	84.0	84.0	120.0
RS	-	80.0	64.0	160.0	112.0	112.0	160.0
RS	-	100.0	80.0	200.0	140.0	140.0	200.0
RS	-	120.0	96.0	240.0	168.0	168.0	240.0
RS	-	150.0	120.0	300.0	210.0	210.0	300.0
RS	-	200.0	160.0	400.0	280.0	280.0	400.0

RIGGING

Roundslings & Endless Webslings

Roundslings available up to 200t capacity

