



Tirak Universal Hoist

Tirak X Series Hoist 3 Phase 400v

- Suitable for man-riding (P-Suffix models only)
- Blocstops and secondary ropes available
- Man-riding pulleys (EN1808)
- 100% Duty Factor
- Rope diameters are bespoke to the size of Tirak machine – lengths available from 20m to 200m

Product Code	Model	Capacity (kg)	Lifting Speed (m/min)	Rope Dia. (mm)	Weight (kg)
H220410500	X500P	500	9	8.3	41.0
H220411030	X1030P	980	9	10.2	45.0
H220412050	X2050P	2000	6	14	100.0
H220423050	X3050M	3000	6	14	105.0



Blocstop BSO

- Fall arrest secondary safety device
- Functions as a secondary back-up brake to control the speed of descent
- Mounts to either the primary or secondary suspension rope

Product Code	Model	For Rope Dia. (mm)	Capacity (kg)	Weight (kg)
H220480500	BSO500	8.3	500	4.6
H220481000	BSO1030	10.3	1000	6.4
H220482000	BSO250	14	2000	13.5



Man-Riding Pulleys EP/EPA

- Conforms to EN 1808 standards for man-riding
- Brand new casing added which works as a limit detection stop as well as a finger protection system
- New casing allows the pulley to be easily opened to fit the wire rope

Product Code	Model	WLL (t)	Bottom of Groove Dia. (mm)	Weight (kg)	Driven Cable Dia. (mm)
H220491016	EPE1.6	1.6	171	3.7	8.3
H220491024	EPE2.4	2.4	196	6.4	10.3
H220491048	EPE4.8	4.8	177.4	14.8	14.0