



## Wire Rope Slings

Wire ropes are widely used as a cost-effective alternative to chains, offering considerably higher capacities and additional properties such as resistance to salt water.

- Multiple configurations – 1, 2, 3, 4, 5 legs and endless
- Multiple terminations – Soft Eyes, Thimble Eyes, Sockets and Swaged Terminals
- Splice options – Talurit, Supersplice, Flemish eye
- Sling types – Single Laid, Cable Laid & Grommets
- Capacities - Grommets up to 6800t minimum breaking load (Double part)

Nominal Dia.	MBL	MBF	Single Leg (t)	WLL 2 Leg		WLL 3/4 Leg		Endless
				0-45°	45-60°	0-45°	45-60°	Chokehitch
8	4.56	44.7	0.8	1.1	0.8	1.7	1.2	1.3
9	5.76	56.5	1.0	1.4	1.0	2.1	1.5	1.6
10	7.12	69.8	1.2	1.7	1.2	2.5	1.8	1.9
13	12.0	118.0	2.0	2.8	2.0	4.2	3.0	3.2
16	18.3	179.0	3.0	4.2	3.0	6.3	4.5	4.8
18	23.0	226.0	4.0	5.6	4.0	8.4	6.0	6.4
20	28.5	279.0	5.0	7.0	5.0	10.5	7.5	8.0
22	34.5	338.0	6.0	8.4	6.0	12.6	9.0	9.6
24	41.0	402.0	7.0	9.8	7.0	14.7	10.5	11.2
26	48.1	472.0	8.0	11.2	8.0	16.8	12.0	12.8
28	55.8	547.0	10.0	14.0	10.0	21.0	15.0	16.0
32	72.9	715.0	13.0	18.2	13.0	27.3	19.5	20.8
36	92.2	904.0	16.0	22.4	16.0	33.6	24.0	25.6
38	103.0	1010.0	18.0	25.2	18.0	37.8	27.0	28.8
40	114.0	1120.0	20.0	28.0	20.0	42.0	30.0	32.0
44	138.0	1351.0	24.0	33.6	24.0	50.4	36.0	38.4
48	164.0	1608.0	29.0	40.6	29.0	60.9	43.5	46.4
52	192.0	1887.0	34.0	47.6	34.0	71.4	51.0	54.4
64	291.0	2855.0	52.0	72.8	52.0	109.2	78.0	83.2
76	411.0	4032.0	73.0	102.2	73.0	153.3	109.5	116.8
92	600.0	5886.0	108.0	151.2	108.0	226.8	162.0	172.8
103	800.0	7848.0	144.0	201.6	144.0	302.4	216.0	230.4
114	939.0	9212.0	169.0	236.6	169.0	354.9	253.5	270.4
128	1138.0	11164.0	204.0	285.6	204.0	428.4	306.0	326.4

Our range of Wire Rope Slings are wide and varied and sizes extend beyond the above table - Please call for details

