



Plate Clamps

CZ Plate Clamps 1t to 30t

- Plate thickness up to 130mm
- Loads lifted must exceed the minimum load to work efficiently and safely
- Pairs of clamps in conjunction with a lifting / spreader beam should be used for longer loads

Product Code	Model	WLL (kg)	Jaw (Z) Capacity (mm)	Dimensions (mm)								Weight (kg)
				A	B	C	D	E	F	G	H	
H540110010	CZ 1	100 - 1000	0 - 20	140	254	51	48	70	83	13	19	4
H540120010	CZ 2	200 - 2000	0 - 32	197	323	67	68	93	110	20	20	11
H540110020	CZ 3	300 - 3000	0 - 32	197	371	80	68	93	110	20	30	12
H540120020	CZ 3L	300 - 3000	30 - 60	228	390	80	68	93	110	20	30	15
H540110030	CZ4	500 - 4000	0 - 32	197	371	80	68	93	129	20	30	12
H540120030	CZ 4L	500 - 4000	30 - 60	228	390	80	68	93	129	20	30	18
H540110040	CZ 6	700 - 6000	0 - 50	293	484	89	95	143	129	25	35	21
H540120040	CZ 6L	700 - 6000	50 - 100	362	524	89	95	143	129	25	35	28
H540110060	CZ 8	950 - 8000	0 - 50	293	492	89	95	143	129	25	42	26
H540120060	CZ 8L	950 - 8000	50 - 100	362	524	89	114	143	129	25	42	32
H540110080	CZ 10	1500 - 10000	0 - 50	293	545	110	95	143	139	25	45	30
H540120080	CZ 10L	1500 - 10000	50 - 100	362	545	110	114	143	139	25	45	37
H540110100	CZ 12	1800 - 12000	0 - 50	360	613	130	125	162	154	30	55	54
H540120100	CZ 12L	1800 - 12000	50 - 100	460	678	130	175	162	154	30	55	63
H540110120	CZ 15	3000 - 15000	0 - 50	360	613	130	125	162	204	45	55	75
H540120120	CZ 15L	3000 - 15000	50 - 100	460	678	130	175	162	204	45	55	88
H540110150	CZ 20	4000 - 20000	0 - 65	462	755	130	165	210	235	45	65	123
H540120150	CZ 20L	4000 - 20000	65 - 130	560	805	130	195	210	235	45	65	136
H540110200	CZ 30	6000 - 30000	0 - 65	462	732	60	165	210	295	65	-	195
H540120200	CZ 30L	6000 - 30000	65 - 130	560	797	60	195	210	295	65	-	295

