



Crane Forks & Material Skips

Self Balancing Crane Fork

- Fork spacing infinitely adjustable manually from 450mm to 950mm
- Bearing ring for weight compensation infinitely adjustable manually or automatically by compression spring
- Working height adjustable by pin system from 1570mm to 1830mm
- Load capacities are quoted for a distance of 680mm between the bale arm and the centre of gravity of the load

Product Code	Load Cap. (kg)	Prong Cross Section (mm)	Effective Height (mm)	Height Under Load (mm)	Prong Length (mm)	Weight (kg)
H520010006	600	40/120	1100-1700	995	1000	160.0
H520010010	1000	40/90	1100-1700	995	1000	185.0
H520010015	1500	40/100	1100-1700	1010	1000	195.0
H520010020	2000	40/120	1100-1700	1065	1000	235.0
H520010030	3000	50/120	1100-1700	1065	1000	270.0



Self-Discharge Boat Skip

- Specifically designed to meet the specific needs of moving waste around site with health and safety in mind
- Bespoke lock and release mechanism on the lifting arm this skip negates the need for personnel to be in the "danger area" while in use
- Automated tipping will increase efficiency and productivity

Product Code	Model	SWL (kg)	Capacity (l)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
H560100500	1045-500	1000	500	1960	1350	550	130.0
H560100750	1045-700	1500	750	2100	1350	645	165.0
H560101000	1045-1000	2000	1000	2200	1600	650	275.0
H560101500	1045-1500	3000	1500	2250	1750	950	425.0
H560102000	1045-2000	4000	2000	2600	1750	950	540.0
H560103000	1045-3000	6000	3000	3100	1950	1000	800.0
H560104000	1045-4000	8000	4000	3250	2050	1200	1320.0