

Hydraulic Cylinders

HHR - Double Acting Hollow Piston Cylinders

The HHR double acting hollow piston cylinder range incorporates all of the design features of the HHS range with the added benefit of double acting design, which greatly enhances speed of operation and performance particularly in the longer length stroke options.



Product Code	Model	Capacity Push (t)	Capacity Pull (t)	Stroke (mm)	Oil Cap (cm ³)	Cyl Eff Area (cm ²)	A (mm)	B (mm)	C (mm)	D (mm)	E	F (mm)	G (Eye bolt)	H (mm)	I (mm)	J (mm)	Weight (kg)
H330340332	HHR302	33	24	51	238	46.7	180	115	60.3	35	4 1/2" - 12un	40	M8	92	28	119	12.2
H330340333	HHR306	33	24	150	701	46.7	279	115	60.3	35	4 1/2" - 12un	40	M8	92	28	218	17.6
H330340334	HHR3012	33	24	305	1424	46.7	434	115	60.3	35	4 1/2" - 12un	40	M8	92	28	373	25.7
H330340612	HHR603	61	38	76	652	85.7	239	160	92	55	6 1/4" - 12un	45	M12	130	31	166	30.6
H330340613	HHR606	61	38	152	1304	85.7	315	160	92	55	6 1/4" - 12un	45	M12	130	31	242	41.6
H330340614	HHR6010	61	38	254	2179	85.7	417	160	92	55	6 1/4" - 12un	45	M12	130	31	344	52.5
H330341022	HHR1003	102	43	76	1087	143.1	310	213	140	80	8 3/8" - 12un	40	M16	178	82	234	68.5
H330341023	HHR1006	102	43	152	2174	143.1	386	213	140	80	8 3/8" - 12un	40	M16	178	82	310	90.0
H330341520	HHR1508	152	71	203	4320	212.8	503	270	184	102	n/a	n/a	n/a	n/a	98	389	170.0
H330342470	HHR2508	247	76	203	7039	346.5	505	350	254	150	n/a	n/a	n/a	n/a	98	389	269.0

JACKING

