



Confined Space Equipment

TR3 Height Adjustable Tripod

Ultra lightweight, tough, and with a durable alloy construction, the TR3 Tripod is primarily to be used as personal protective equipment, to provide access or fall protection in confined space environments.

- Pulleys are protected from damage by an extended crown
- Spring Loaded Sliding Pulleys for ease of setup and retaining pin to prevent cable coming off the pulley
- Automatic leg lock out catches with trigger release

Product Code	Model	Capacity	Description	Height		Weight (kg)
				Overall (mm)	Lifting Point (mm)	
H440710001	TR3	250kg	Height Adjustable Tripod	1400 - 2400	1200 - 2200	14.7



PPEW2000 Man Riding / Material Winch

The PPEW2000 functions as a secondary back up device where there is no assistance for the descent such as a ladder. An essential piece of equipment to meet the requirements of the EN 795 Class B Standard.

- 250kg capacity
- 20m lift
- Harken lokhead fibre rope capstan winches are also available for longer lengths. Hoisting speed can be increased by using a portable power tool

Product Code	Model	Description	Weight (kg)
H440810001	PPEW2000	Man Riding / Material Winch	8.5



FABX2R & FABXLR Recovery Blocks

- The FABX2R & FABXLR function as standard Fall Arrest Block, but in the event of a fall, the rewind/rescue mechanism can be engaged to raise and/or lower a fallen worker
- Fitted as standard with a bracket to suit either the TR3 Tripod or the PGR Porta Gantry Rapide

Product Code	Model	Description	Weight (kg)
H440410001	FABXR-18C	18m/60ft Fall Arrest Block with recovery (galv wire)	9.4
H440410002	FABXLR	40m/130ft Fall Arrest Block with recovery (galv wire)	16.5

