



Electric Chain Hoists

CM Lodestar Electric Chain Hoists

The Lodestar hoist is a tough and durable electric chain hoist, designed to keep working in the most arduous applications. This hoist is recognised and proven within the hire industry as the number one hoist, where high duty, combined with long heights of lift are required.

- Range from 0.25t to 3t
- Adjustable upper and lower limit switches
- 48V control, IP65 pendant as standard
- Thermal overload protection as standard

Product Code	Model	Operating Voltage	Capacity (WLL) (kg)	No. of Falls of Load Chain	Lifting Speed (s) (m/min)	Weight at Std HOL (kg)	Weight for Extra Metre HOL (kg)
H010200021	G	230V or 110V 1ph 50Hz	250	1	8	29.0	0.8
H010200051	F	230V or 110V 1ph 50Hz	500	1	4	29.0	0.8
H010200051	J	230V or 110V 1ph 50Hz	500	1	8	51.0	1.4
H010200103	L	230V or 110V 1ph 50Hz	1,000	1	4	52.0	1.4
H010200103	LL	400V 3ph 50Hz	1,000	1	8	52.0	1.4
H010200103	LL2	400V 3ph 50Hz	1,000	1	8/2.5	53.0	1.4
H010200203	R	230V or 110V 1ph 50Hz	2,000	2	2	58.0	2.8
H010200203	RR	400V 3ph 50Hz	2,000	2	4	58.0	2.8
H010200203	RR2	400V 3ph 50Hz	2,000	2	4/1.3	59.0	2.8
H010200303	RT	230V or 110V 1ph 50Hz	3,000	3	1.33	64.0	4.2

Model	A (mm)	B (mm)	C (mm)	D (mm)	F (mm)	H (mm)	J (mm)	L (mm)	M (mm)	P (mm)	AP (mm)
Lodestar 250/500	413	156	17	279	197	25	100	122	25	168	235
Lodestar 500/1000	471	194	22	241	271	30	138	184	28	198	271
Lodestar 2000	613	194	28	241	271	38	165	157	33	198	284
Lodestar 3000	750	194	28	241	271	38	165	157	33	198	319

