



Tirfor Machines, Ropes & Accessories

Tirfor TU Heavy Duty Series (manually operated)

- For lifting, pulling and positioning heavy loads
- Unrivalled in terms of durability and sturdiness
- Extra shear pins in handle
- Rope sold separately
- T5 medium duty machines also available

Product Code	Model	WLL (kg)	Maxiflex Rope Dia. (mm)	Rope Breaking Strain (kg)	Machine Weight (kg)	(20m) Rope Weight (kg)
H220110008	TU8	800	8.3	5500	8.4	6.1
H220110016	TU16	1600	11.5	9200	20.0	13.1
H220110030	TU32	3200	16.3	16,000	26.8	23
H220120035	T35	3200	16.3	16,000	26.8	23
H220110054	RW54	5400	-	-	57	-



Maxiflex Wire Ropes

- Maxiflex ropes have been specifically designed to suit Tirfor products
- The rope is manufactured to extremely high tolerances which are necessary for the reliable operation of the product mechanism inside the machine, especially when lowering under load
- Using Maxiflex Ropes is part of the certification of the machine

Maxiflex Wire Rope	TU-8 / T508 Fitted with Hook 8.3 Dia. (mm)	TU-16 / T516 Fitted with Hook 11.3 Dia. (mm)	TU-32 / T532 / T35 Fitted with Hook 16.3 Dia. (mm)	RW54 Fitted with Hook 20 Dia. (mm)
Length (m)	Product Code	Product Code	Product Code	Product Code
20	H220800820	H220811620	H220823220	H220720020
40	H220800840	H220811640	H220823240	H220720040
60	H220800860	H220811660	H220823260	H220720060
80	H220800880	H220811680	H220823280	H220720080
100	H220800900	H220811700	H220823300	H220720100

Other lengths available on request

Up to 80m - 5 strand rope. Above 80m - 6 strand rope. All Tirfor machines are supplied fully tested and certified in accordance with the statutory regulations. The TU16H and TU32H Tirfor machines must not be used for man-riding applications.

Accessories



Coni Clamp



Ground Anchor



Drum Reeler