

Fall Arrest Blocks

FAB3W

The FAB3W is a lightweight palm-sized Fall Arrest Block and is so light it can be mounted directly onto the user's harness via the rear D connector. Also available as a dual assembly for 100% tie off whilst moving between anchorages whilst moving around a structure.

| Product Code | Model | Length (m) | Length (ft) | Description | Weight (kg) |
|--------------|-------|---------------|----------------|------------------------|----------------|
| H440600003 | FAB3W | 3 | 10 | Fall Arrest Block (EN) | 1.1 |



FABX1-10C

The FABX1 is available with galvanised or stainless steel cable, Dyneema fibre rope or Dyneema webbing. Up to 10m (33ft) in length the FABX1 offers lightweight handling, excellent serviceability and exceptional performance.

| Product Code | Model | Length (m) | Length (ft) | Description | Weight (kg) |
|--------------|-----------|---------------|----------------|--|----------------|
| H440600010 | FABX1-10C | 10 | 33 | Fall Arrest Block Galvanised Wire (EN) | 4.1 |



FABX2-15C & FABX2-18C

The FABX2 is available with galvanised or steel cable. Up to 18m in length the FABX2 offers lightweight handling, excellent serviceability and exceptional performance.

| Product Code | Model | Length (m) | Length (ft) | Description | Weight (kg) |
|--------------|-----------|---------------|----------------|--|----------------|
| H440600015 | FABX2-15C | 15 | 49 | Fall Arrest Block Galvanised Wire (EN) | 6.2 |
| H440600018 | FABX2-18C | 18 | 59 | Fall Arrest Block Galvanised Wire (EN) | 6.4 |

