Heavy-Duty Bow Shackles

Heavy-Duty Green Pin Bow Shackle

- Body and pin high tensile steel, Grade 8, quenched and tempered
- Safety Factor: MBL equals 5 x WLL
- EC declaration of conformity
- Plus 5% forging tolerance on inside width and length

Product Code	Working Load Limit (t)	Body Dia. (mm)	Pin Dia. (mm)	Eye Dia. (mm)	Inside Width (mm)	Inside Length (mm)	Bow Width (mm)	Overall Length (mm)	Bolt Length (mm)	Overall Width (mm)	Weight Each (kg)
H550211200	120	95	95	208	147	400	238	667	440	428	110.0
H550211500	150	105	108	238	169	410	275	688	490	485	160.0

Wide Body Sling Shackles

- Bow and pin alloy steel, grade 8, quenched and tempered
- Safety Factor: MBL equals 5 x WLL
- Temp -20°C to 200°C
- Wide body profile to protect slings

Product Code	Working Load Limit (t)	Body Dia. (mm)	Pin Dia. (mm)	Eye Dia. (mm)	Inside Width (mm)	Inside Length (mm)	Bow Width (mm)	Overall Length (mm)	Bolt Length (mm)	Overall Length (mm)	Weight Each (kg)
H550220075	75	68	70	125	110	290	185	473	327	317	48
H550220125	125	85	80	154	137	366	220	583	426	390	92
H550220150	150	94	95	179	147	391	253	645	435	434	140
H550220200	200	110	105	199	158	481	280	759	470	482	205
H550220250	250	126	120	227	179	542	300	859	519	530	264
H550220300	300	135	134	245	195	601	350	947	575	620	360
H550220400	400	160	160	293	231	576	370	985	675	690	580
H550220500	500	170	180	328	263	681	450	1131	748	790	780
H550220600	600	190	200	348	289	741	490	1234	809	865	980
H550220700	700	200	215	392	315	751	540	1284	879	901	1360
H550220800	800	218	230	420	342	851	554	1426	942	947	1430
H550220900	900	242	255	466	368	851	580	1488	1023	1023	1650
H550221000	1000	260	270	490	399	851	614	1532	1103	1107	2970
H550221250	1250	285	300	510	452	931	650	1666	1227	1182	3700
H550221550	1550	285	320	550	483	950	680	1710	1300	1253	4000

**These sizes are utilised for the digital load indicators on page 132*