



## Material Lifts & Accessories

### Genie Superlift Advantage

Choose base, mast height, winch speed & load handling attachments to configure the exact material lift for your work site.

- Heavy-duty design
- Patented telescoping mast system with mast brake
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Compact design, legs fold up for easy storage
- Roller wheels allow easy transport in stowed position
- Easy to load and unload on or off a vehicle for transport

Product Code	H450010010	H450010015	H450010020	H450010025
Model	SLA-10	SLA-15	SLA-20	SLA-25
Measurements	Metric	Metric	Metric	Metric
Working Height: Standard Forks- Down	2.97m	4.46m	5.94m	7.42m
Working Height: Standard Forks- Up	3.49m	4.98m	6.46m	7.94m
Working Height: Adjustable Forks- Down	2.97m	4.46m	5.94m	7.42m
Working Height: Adjustable Forks- Up	3.49m	4.98m	6.46m	7.94m
Working Height: Flat Forks	2.97m	4.46m	–	–
Working Height: Boom	3.28m	4.76m	6.25m	7.42m
Working Height: Load Platform- Forks Down	2.97m	4.46m	5.94m	7.42m
Working Height: Load Platform- Forks Up	3.49m	4.98m	6.46m	7.94m
Height- Stowed	2.0m	2.0m	2.0m	2.0m
Length- Stowed	74cm	74cm	74cm	79cm
Length- Operating	1.51m	1.88m	2.08m	2.08m
Width- Stowed	80cm	80cm	80cm	80cm
Width- With Stabilisers Lowered	1.85m	1.85m	1.85m	1.85m
Width- Straddle Base Minimum	80cm	80cm	–	–
Width- Straddle Base Maximum	1.47m	1.47m	–	–
Width- Straddle Base Maximum Inside	1.27m	1.27m	–	–
Ground Clearance	5cm	5cm	5cm	5cm
Load Height Minimum	15cm	15cm	15cm	15cm
Front Casters	10cm	10cm	10cm	10cm
Rear Casters	13cm	13cm	13cm	13cm
Load Capacity 46cm (18in) Load Centre	454kg	363kg	363kg	295kg
Load Capacity 61cm (24in) Load Centre	454kg	363kg	272kg	204kg
Load Capacity 107cm (42in) Load Centre	181kg	227kg	159kg	113kg
Average Cranks Standard Winch	27.8 cranks/m	27.8 cranks/m	27.8 cranks/m	27.8 cranks/m
Weight Standard	118kg	151kg	184kg	204kg
Weight Straddle Base	137kg	163kg	–	–



### Standard Forks (Down)

A variety of general loads. Get an additional 21in (53cm) of lift by turning over and re-pinning the forks.

## Material Lift Accessories

A range of interchangeable load handling attachments to cater for a large variety of requirements to ensure that your Genie SLA is equipped correctly for the job in hand.

Load Handling Attachments			
Product Code	Model	Dimensions L/W/D (mm)	Weight (kg)
H450020001	Boom	1070 x 40 x 165	18.0
H450020002	Pipe Cradle	700 x 620 x 150	4.5
H450020003	Fork Extensions (Attached)	640 x 50 x 80	2.0
H450020004	Adjustable Forks	700 x 760 x 60	24.0
H450020005	Flat Forks	810 x 790 x 38	36.0
H450020006	Load Platform	700 x 580 x 70	14.0



### Boom

Option to transform your lift into a mobile, vertical crane or hoist to position tooling fixtures, circuit breakers, engines and more.



### Pipe Cradle

An ideal accessory for lifting round pipes and/or odd shaped items into position.



### Fork Extensions

Insert onto standard forks for an additional 25in (64cm) of length.



### Adjustable Forks

Widen from 11.5in to 30in (29cm to 76cm) to accommodate diverse loads.



### Flat Forks

Widen from 16in to 31in (41cm to 79cm) to provide proper support, allow you to easily lift your load off of flat surfaces.



### Load Platform

Fits over the forks to handle odd-sized or heavy objects — no tools required for installation.