



Hand Chain Hoists

SS12 Corrosion Resistant Chain Hoist

- Range from 0.5t to 30t
- Fully corrosion protected body and components
- Corrosion protected load and hand chain
- Marine specific friction discs
- Stainless steel fixings and fasteners
- Certified 2% light load protection
- Operating temperature of -40°C to +50°C
- Standard lift height 3m, 6m, 9m, 12m HOL or can be chained to meet your requirements

Product Code	Model	Capacity (t)	Effort (kg)	Dimensions (mm)							Load Chain		Std HOL (m)	Weight at Std HOL (kg)	Weight for Extra Metre HOL (kg)
				A	B	D	E	F1	F2	G	Diameter (mm)	No. of Falls			
H010110003	SCB-0050	0.5	21	93	66	52	78	24	38	305	6.3	1	3	10.8	1.8
H010110103	SCB-0100	1.0	25	93	66	63	87	28	45	340	6.3	1	3	11.8	1.8
H010110153	SCB-0150	1.5	32	98	73	78	102	34	51	385	7.1	1	3	16.2	2.1
H010110203	SCB-0200	2.0	34	101	79	87	113	35	53	420	8.0	1	3	20.0	2.4
H010110303	SCB-0300	3.0	38	109	84	98	157	36	56	550	10.0	1	3	30.6	3.2
H010110503	SCB-0500	5.0	37	101	79	122	209	49	70	575	8.0	3	3	37.8	5.2
H010111003	SCB-1000	10.0	40	109	84	153	263	54	87	660	10.0	3	3	64.0	7.5
H010112003	SCB-2000	20.0	43	161	90	148	360	81	110	1050	10.0	6	3	178.7	14.2
H010113003	SCB-3000	30.0	42	220	220	388	388	91	135	1200	10.0	10	3	306.9	23.8

