



## Counterbalanced Material Lifts

### SLK

- Integral counterweights avoid the need for forward outriggers allowing the user to bring loads directly to walls or high lying porches
- Ideal for handling awkward loads into place such as window panes and glazing
- Specialist accessories and functionality for handling glass are available on request
- All standard Superlift accessories are available

Product Code	H450050010	H450050015	H450050020	H450050025
Model	SLK10	SLK15	SLK20	SLK25
Lifting Height - Standard Forks Up (mm)	3500	5000	6500	7900
Height - Stowed (mm)	2040	2040	2040	2040
Length - Stowed (mm)	900	900	960	1020
Length - Working Position (mm)	1500	1800	2220	2220
Width - Stowed (mm)	800	800	800	800
Width - Working Position (mm)	2200	2200	2200	2200
Ground Clearance - Working Position (mm)	80	80	80	80
Loading Height min (mm)	270	270	270	270
Pay Load (kg)	450	360	360	300
Weight Basic Chassis (kg)	118.0	144.0	184.0	204.0
Weight Complete with Counterbalance Weights (kg)	246.0	272.0	312.0	332.0



## Heavy Capacity Counterbalanced Material Lifts

### GML800+

- Simple to transport, set up and use
- Vastly increased lifting capacity over the standard Superlift range - up to 900kg dependant on model and load centre position
- Integral counterweights avoid the need for forward outriggers allowing the user to bring loads directly to walls or high lying porches
- All standard Superlift accessories are available
- Specialist accessories and functionality for handling glass are available on request

Product Code	Model	Working Height Standard Forks Up (mm)	Transport Position Height/Length/Width (mm)	Working Position Height/Length/Width (mm)	Safe Working Load (kg)	Weight Chassis + Outriggers (kg)
H450060010	GML800+/10	3490	1980/1000/0780	1980/1940/0780	900	237.0 - 273.0
H450060015	GML800+/15	4980	1980/1000/0780	1980/1940/0780	850	260.0 - 296.0
H450060020	GML800+/20	6460	1980/1000/0780	1980/1940/0780	850	293.0 - 329.0
H450060025	GML800+/25	7940	1980/1000/0780	1980/1940/0780	800	316.0 - 352.0