

# Hydraulic Cylinders

## HHS - Single Acting Hollow Piston Cylinders



- Spring assisted return
- Optional piston rod saddles
- Collar thread protector supplied as standard
- Range from 11t to 102t capacity
- Stroke lengths from 25mm to 152mm
- Working pressure 700 Bar

JACKING

Product Code	Model	Capacity (t)	Stroke (mm)	Oil Cap (cm <sup>3</sup> )	Cyl Eff Area (cm <sup>2</sup> )	A (mm)	B (mm)	C (mm)	D (mm)	E	F (mm)	G (Eyebolt)	H (mm)	I (mm)	Weight (kg)
H330340110	HHS101	11	25	39	15.8	110	70	38	20	2 3/4" - 16un	30	M8	51	19	2.8
H330340111	HHS102	11	50	79	15.8	140	70	38	20	2 3/4" - 16un	30	M8	51	19	3.0
H330340112	HHS106	11	152	240	15.8	297	70	38	20	2 3/4" - 16un	30	M8	51	19	10.2
H330340230	HHS202	23	50	167	33.3	160	100	51	30	3 7/8" - 12un	40	M8	82.5	31	7.0
H330340231	HHS206	23	150	500	33.3	306	100	51	30	3 7/8" - 12un	40	M8	82.5	31	13.8
H330340330	HHS302	33	50	233	46.7	165	115	60	35	4 1/2" - 12un	40	M8	92	31	10.6
H330340331	HHS306	33	152	710	46.7	320	115	60	35	4 1/2" - 12un	40	M8	92	31	19.2
H330340610	HHS603	61	76	651	85.7	226	160	92	55	6 1/4" - 12un	59	M12	130	31	28.0
H330340611	HHS606	61	150	1285	85.7	315	160	92	55	6 1/4" - 12un	59	M12	130	31	40.6
H330341020	HHS1003	102	76	1088	143.1	276	213	127	81	8 3/8" - 12un	60	M16	178	45	64.0
H330341021	HHS1006	102	150	2147	143.1	350	213	127	81	8 3/8" - 12un	60	M16	178	45	75.0

