



# Hand Chain Hoists

## TCB14 Chain Hoist

- Range from 0.5t to 30t
- Rugged construction yet lightweight and portable
- Patented quad cam mechanical brake
- Certified 2% light load protection
- Operating temperature of -40°C to +50°C
- Proof tested to 1.5 times rated capacity
- Standard lift height 3m, 6m, 9m, 12m HOL or can be chained to meet your requirements
- Tested and certified for “fleeting” and “cross-hauling” application

Product Code	Model	Capacity (t)	Effort (kg)	Dimensions (mm)							Load Chain		Std HOL (m)	Weight at Std HOL (kg)	Weight for Extra Metre HOL (kg)
				A	B	D	E	F1	F2	G	Diameter (mm)	No. of Falls			
H010100003	CB-0050	0.5	21	93	66	52	78	24	38	305	6.3	1	3	10.8	1.8
H010100103	CB-0100	1.0	25	93	66	63	87	28	45	340	6.3	1	3	11.8	1.8
H010100203	CB-0200	2.0	34	101	79	87	113	35	53	420	8.0	1	3	20.0	2.4
H010100303	CB-0300	3.0	38	109	84	98	157	36	56	550	10.0	1	3	30.6	3.2
H010100303	CB-030T	3.0	34	98	73	60	148	36	56	465	7.1	2	3	23.3	3.2
H010100503	CB-0500	5.0	37	101	79	122	209	49	70	575	8.0	3	3	37.8	5.2
H010101003	CB-1000	10.0	40	109	84	153	263	54	87	660	10.0	3	3	64.0	7.5
H010101503	CB-1500	15.0	41	109	84	225	378	59	81	840	10.0	5	3	128.5	11.8
H010102003	CB-2000	20.0	43	161	90	148	360	81	110	1050	10.0	6	3	178.7	14.2
H010103003	CB-3000	30.0	42	220	220	388	388	91	135	1200	10.0	10	3	306.9	23.8

